ELECTRICAL & ELECTRONIC

ELECTRIC MOTOR DEGREASER

preserve, protect, prevent



703

DS

FAST EVAP

ALECTRIC MOTOR DEGREASER Desengrasador de Notores Eléctricos

E703

E anars wee recover were (ADVENTENDA company recovered) may eet on an repraries ust any retrieve and an and rectange and part. Recause a by repraries 19 oz (1 1b 3 oz) • 5399

NON

NSE K2

NON FLAM

KB

92

For use on Energized Equipment

NSF® Registered; K2 Rated (Solvents for cleaning electronic instruments)(Reg# 118283)

Dielectric strength value: 39,500 volts

Non-Flammable

Fast evaporation rate

KB Solvency Strength (higher value, stronger the solvent): 92

HMIS Hazard Rating: Health (2) • Flammability (0) • Reactivity (0)

- Non-flammable
- Leaves no residue
- Dielectric strength: 39,500 volts



PRESERVE. PROTECT. PREVENT."

Sprayon[®] EL[™]703 Electric Motor Degreaser instantly penetrates and removes dirt, oil, grease, wax and moisture from electrical equipment and machinery. Formulated to clean and/or degrease electrical equipment when electrical current exists or when there is a residual electrical potential from a component, such as a capacitor. Evaporates completely, leaving no residual film and is equipped with an extension tube for hard-to-reach areas.

ELECTRICAL & ELECTRONIC

USES

- Switches & relays
- Communicators
- Transmitters
- Tooling
- Antenna insulators
- Molds
- Motors
- Machinery & equipment
- Controls
- Printed circuits
- Gold & silver
- Fuse holders
- Oscillators
- Radar equipment

APPLICATION

Product should be used in a well ventilated area. Saturate area to be cleaned until all grease and dirt are thoroughly wet. Let it soak for a few minutes and then wipe clean with rag. After dirt has been wiped away, allow to air-dry. In extreme cases, a second application may be necessary. NOTE: May harm certain plastics, elastomers and air-dry painted surfaces. Test product on non-essential similar material prior to application.

PERFORMANCE

EVAPORATION RATE: Fast KB VALUE (Cleaning Power): 92 DIELECTRIC STRENGTH: 39,500 volts PLASTIC SAFE: No

- NSF Registration Number 118283; K2 Rated
- Leaves no residue
- Non-corrosive
- Non-staining
 Equipped wit
- Equipped with an extension tube for hard-to-reach areas

PACKAGING

STOCK #: S00703 UPC CODE: 0-75577-90703-8 FILL WT: 19 oz. PER CASE: 12 CARTON DIMENSIONS: L 11.13" x W 8.44" x H 9.94"

PROPERTIES

APPEARANCE: Clear Volatile Liquid ODOR: Strong PROPELLANT: CO₂ WT./GAL.: 13.33 SPECIFIC GRAVITY: 1.60 H.A.P.S. (HAZARDOUS AIR POLLUTANTS): No SARA 313 CHEMICALS: No % VOC AEROSOL: 0% V.O.C. COMPLIANT CALIFORNIA: Yes V.O.C. COMPLIANT OTC STATES: Yes FLAMMABLE: No FLASH POINT: N/A HAZARD RATING: 2, 0, 0 SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS: sprayon.com CUSTOMER SERVICE: 1-800-777-2966 TECHNICAL INFORMATION: 1-800-251-2486

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



© 2010 Sprayon[®] Products Made in U.S.A.

Distributed by:



PRESERVE. PROTECT. PREVENT.



Sprayon[®] Products 101 Prospect Ave. NW Cleveland, OH 44115 Sprayon.com 1-800-777-2966